

Easystart Part No.	Volts	Capacity AH @ 20HR	C.C.A. (SAE)	C.C.A. (EN2)	Plates per cell	Reserve capacity (minutes)	Dimensions (Metric)			Dimensions (Imperial)			Weight (kg)	Layout	Terminal type	Hold down
							L	W	H	L	W	H				
615R	12	100	720	680	TBA	TBA	408	173	233	16.06	6.81	9.17	TBA	0	T1	N
616	12	100	720	680	TBA	TBA	400	175	205	15.74	6.89	8.07	TBA	1	T1	N
643	12	95	680	650	15	165	320	175	225	12.60	6.89	8.86	27	0	T1	N
644	12	99	680	650	15	165	320	175	225	12.60	6.89	8.86	27	1	T1	N
663	12	112	760	720	17	185	320	175	225	12.60	6.89	8.86	30	0	T1	N
664	12	112	760	720	17	185	320	175	225	12.60	6.89	8.86	30	1	T1	N
622	12	135	850	800	21	210	513	223	223	20.19	8.78	8.78	42	3	T1	N
623	12	135	900	850	23	210	513	223	223	20.19	8.78	8.78	42	4	T1	N
624	12	210	1150	1090	31	400	512	270	240	20.15	10.63	9.45	56	4	T1	N
625	12	210	1150	1090	31	400	512	270	240	20.15	10.63	9.45	56	3	T1	N
625S	12	225	1250	1180	35	440	512	270	240	20.15	10.63	9.45	59	3	T1	N
627	12	130	900	860	21	230	513	189	224	20.19	7.44	8.82	44	3	T1	N
627R	12	130	900	860	21	230	513	189	224	20.19	7.44	8.82	44	4	T1	N
627S	12	148	950	900	25	260	513	189	224	20.19	7.44	8.82	48	3	T1	N
629	12	180	1020	970	25	350	513	223	223	20.19	8.78	8.78	46	3	T1	N
629S	12	192	1200	1140	31	380	513	223	223	20.19	8.78	8.78	49	3	T1	N
630	12	120	680	640	21	200	513	189	224	20.19	7.44	8.82	44	3	T1	B3
647	12	110	800	760	17	200	330	178	275	12.99	7.00	10.82	31	0	T1	N
648	12	110	800	760	17	200	330	178	275	12.99	7.00	10.82	31	1	T1	N
655	12	125	830	790	19	240	330	178	275	12.99	7.00	10.82	34	0	T1	N
656	12	125	830	790	19	240	330	178	275	12.99	7.00	10.82	34	1	T1	N