

Motorcycle Battery Specifications

Part number	Din ref	Voltage	Capacity AH (10HR)	Cold cranking amps	Bench charge rate	Dimensions			Layout	Terminal
						Length	Width	Height		
6N2-2A-4	002-11	6	2	NA	0.2	70	46	95	1	wire
6N4-2A-2	004-14	6	4	NA	0.4	70	70	95	2	wire
6N4-2A-4	004-14	6	4	NA	0.4	70	70	95	2	wire
6N4A-4D	004-13	6	4	NA	0.4	60	58	130	3	wire
6N4B-2A	004-12	6	4	NA	0.4	100	47	96	2	wire
6N6-3B	006-12	6	6	NA	0.6	99	57	110	4	column
B39-6	007-14	6	7	NA	0.7	126	48	126	5	column
B49-6	008-11	6	10	NA	1.0	91	83	160	6	column
6N11A-1B	011-99	6	11	NA	1.1	122	62	132	7	column
6N11A-4	NA	6	11	NA	1.1	122	62	132	8	column
12N5.5-3B	506-11	12	5.5	55	0.5	138	61	131	3	column
12N5.5-4B	NA	12	5.5	55	0.5	138	61	131	5	column
12N5.5A-3B	506-12	12	5.5	44	0.5	104	91	115	3	column
YB2.5L-C	503-11	12	2.5	25	0.2	81	71	105	1	wire
YB3L-A	503-12	12	3	32	0.3	98	57	111	2	column
YB3L-B	503-13	12	3	32	0.3	98	57	111	3	column
YB4L-A	NA	12	4	50	0.4	120	70	92	2	cube
YB4L-B	504-11	12	4	50	0.4	120	70	92	3	cube
YB5L-B	505-12	12	5	55	0.5	120	61	130	3	cube
YB7-A	508-13	12	8	90	0.8	137	77	132	4	column
YB9A-A	NA	12	9	130	0.9	137	77	155	4	column
YB9-B	509-14	12	9	130	0.9	135	75	139	5	column
YB9L-B	509-15	12	9	130	0.9	137	76	139	3	column
YB9L-A2	509-16	12	9	124	0.9	135	75	139	2	cube
YB10L-A2	511-12	12	11	160	1.1	135	90	145	2	cube
YB10L-B2	511-13	12	11	160	1.1	135	90	145	3	cube
YB12A-A	512-11	12	12	165	1.2	134	80	160	4	column
YB12A-B	512-15	12	12	165	1.2	134	81	162	5	column
YB12AL-A2	512-13	12	12	165	1.2	135	81	162	2	column
YB12B-B2	512-12	12	13	165	1.3	159	89	129	5	cube
YB14-A2	514-12	12	14	190	1.4	134	89	166	4	cube
YB14-B2	514-14	12	14	190	1.4	134	89	166	5	cube
YB14L-A2	514-11	12	14	190	1.4	134	89	166	2	cube
YB14L-B2	514-13	12	14	190	1.4	134	89	166	3	cube
YB16AL-A2	516-11	12	16	175	1.6	205	70	162	4	cube
YB16B-A	516-15	12	16	175	1.6	160	90	159	4	cube
HYB16A-A	516-12	12	16	150	1.6	146	88	180	4	cube
YB18-A	NA	12	18	235	1.8	181	90	164	4	cube
YB18L-A	519-14	12	18	235	1.8	181	90	164	2	cube
YB16-B	519-12	12	19	240	1.9	175	100	155	5	column
YB16L-B	519-11	12	19	240	1.9	175	100	155	3	column
YB16CL-B	519-19	12	19	240	1.9	175	100	175	3	cube
Y50-N18L-A	520-12	12	20	260	2.0	205	90	162	2	cube
12N24-3	525-15	12	24	260	2.4	184	126	173	7	column
12N24-4	524-98	12	24	260	2.4	184	126	173	6	column
YB30L-B	NA	12	30	300	3.0	168	132	176	3	cube
YB30CL-B	NA	12	30	300	3.0	168	132	192	3	cube
YTR4A-BS	NA	12	2.3	25	0.2	113	48	85	8	cube
YTX4L-BS	504-95	12	3	40	0.3	114	70	85	7	cube
YTX5L-BS	505-96	12	4	55	0.4	114	70	105	7	cube

YTX7L-BS	507-94	12	6	75	0.6	114	70	130	7	cube
YTX9-BS	508-12	12	8	90	0.8	151	87	106	6	cube
YTX12-BS	512-97	12	10	160	1.0	151	87	130	6	cube
YT12A-BS	NA	12	10	120	1.0	151	87	106	6	cube
YTX14-BS	514-96	12	12	180	1.2	151	87	146	6	cube
YTX20-BS	NA	12	18	210	1.8	175	86	154	6	cube
YTX20L-BS	520-97	12	18	210	1.8	175	86	154	7	cube
YTZ7-S	NA	12	6	40	0.6	113	70	105	7	cube
YT7-B4	507-91	12	6	60	0.6	150	65	92	6	cube
YTZ10-S	NA	12	8.5	100	0.9	150	65	102	6	cube
YTZ12-S	NA	12	11	115	1.1	150	87	110	6	cube
YT12B-4	512-91	12	11	95	1.1	150	69	130	6	cube
YTZ14-S	NA	12	12	115	1.2	150	87	110	6	cube
YT14B-4	NA	12	13	110	1.3	150	69	145	6	cube